



We provide safety NATURAL SMOKE EXHAUST SYSTEM

Ensuring the safety of users is one of the key requirements affecting the design of each building. Staircases are the main way of safe evacuation of people, that is why it is so important to equip them with an efficient smoke exhaust system. It is used to remove smoke, fire gases and heat energy generated during a fire from the building.

In the mcr THERM SYSTEM natural smoke exhaust system for staircases, which can be found in the "MERCOR" S.A. offer, we have used a number of innovative devices. These solutions are the result of our many years of research, improvements and industry experience. They contribute to the protection of life and property, while meeting current and future requirements for the thermal insulation of buildings. Their aesthetics and handling can meet the expectations of even the most demanding users and fit perfectly into the context of modern architecture.

The complete stairwell smoke extraction system proposed by "MERCOR" S.A. consists of devices for smoke extraction, aeration and ventilation as well as control devices.

Mercor

Mercor Group's mission is to deliver safety to building users by providing them with comprehensive fire protection. For over 35 years, we have been offering our business partners, at every stage of the investment process, products and services they can always trust. As a leader of modern technologies in the fire protection industry, we introduce new solutions that are ahead of the norm, and are additionally characterized by high quality and aesthetic workmanship.

> staircases with mcr ULTRA THERM

mcr THERM SYSTEMS

SYSTEM'S ADVANTAGES

FUNCTION

The system ensures safe evacuation through the staircase, while offering additional natural ventilation and enabling access to the roof (vent with hatch function).





QUALITY

It is the result of combining the unique features of the mcr THERM SYSTEM: functionality, aesthetics and advanced technology, and the system is made of materials with high quality parameters.

WARMTH

The use of innovative products (smoke vents and windows) with high insulation, without thermal bridges guarantees no heat loss.



RELIABILITY

Devices included in the system (vents and windows) have been tested in 10 000 cycles to the position of ventilation.

FRIENDLY SERVICE

Notifications from the system control panel make it possible to quickly determine the causes of errors, and the design of the control panel mainboard allows the system to be expanded with additional functions or devices.

Simplicity and modern design make the de-

AESTHETICS

vices easy to integrate into interior design, adapting them to buildings of various character and purpose.


INTUITIVE SERVICE

One control panel is used for configuration and diagnostics of all devices in the system, the advantage is also the possibility of continuous monitoring of the system operation from the front panel of the control panel.

The **mcr ULTRA THERM** smoke vents (part of mcr THERM SYSTEMS) have obtained a declaration showing the environmental impact of the product – from sourcing of raw materials to transport and final assembly.









DEVICES FOR SMOKE EXHAUST AND VENTILATION

Smoke exhaust vent mcr ULTRA THERM

Function: smoke exhaust, daily ventilation **Dimensions min.:** 100 x 100 cm or 80 x 120 cm **Dimensions max.:** 200 x 300 cm

Design: modular PVC base or folded steel base **Glazing:** multi-chamber polycarbonate plates, acrylic or solid polycarbonate domes, mixed glazing **Control:** electric 24 V-/48 V-/230 V~







Smoke exhaust vent mcr ULTRA THERM

Dimensions min.: 100 x 100 cm or 90 x 120 cm

Dimensions max.: 160 x 220 cm (1 actuator) or

Design: modular PVC base or folded steel base

Glazing: multi-chamber polycarbonate plates,

Control: electric 24 V-/48 V-/230 V~

acrylic or solid polycarbonate domes, mixed glazing

Function: smoke exhaust, daily ventilation, roof access

200 x 250 cm (2 actuators)

(with roof access function)









Smoke exhaust windows mcr OSO THERM 75

Function: smoke exhaust and daily ventilation
Dimensions min.: 80 x 80 cm
Dimensions max.: 270 x 130 cm or 160 x 220 cm
Design: thermally broken multi-chamber aluminium profiles
Glazing: glazing unit or sandwich panel
Control: electric 24 V-/48 V-/230 V~

Aeration window mcr OSO THERM 75

Function: aeration and daily ventilation
Dimensions min.: 80 x 80 cm
Dimensions max.: 270 x 130 cm or 160 x 220 cm
Design: thermally broken multi-chamber aluminium profiles
Glazing: glazing unit or sandwich panel
Control: electric 24 V-/48 V-/230 V~

ELECTRIC CONTROL SYSTEM DEVICES



Control unit mcr SVM

mcr SVM 24V- 5 A / mcr SVM 24- 8 A In accordance with EN12101 – class A (double power supply)

Power supply voltage: 230 V~ (1.2 A/1.7 A) Output voltage: 24 V-No. of outputs: 1 (1 fire zone / 1 comfort ventilation group) Max. total load: 5 A / 8 A Operation time without main voltage source: 72 h Dimensions: 238 x 113 x 286 mm

Control unit mcr SV-ds

mcr SV 24V-xx-ds / mcr SV 48V-xx-ds In accordance with EN12101 – class A (double power supply)

Power supply voltage: 230 V~ (5 A/10 A) Output voltage: 24 V- or 48 V-No. of outputs: 2 (2 fire zones / 2 comfort ventilation groups) Max. total load: 8 A / 24 A / 30 A / 32 A Operation time without main voltage source: 72 h Dimensions: 343 x 178 x 450 mm





"MERCOR" S. A. ul. Grzegorza z Sanoka 2 80-408 Gdańsk, Poland tel. + 48 58 341 42 45 export@mercor.com.pl

MERCOR UKRAINE SP. Z O.O. Ukraine

www.mercor.com.ua

- Scheptyckich 26
- 9-016 Lviv
- +380 32 240 34 47
- S +380 32 240 34 07
- 🖂 info@mercor.com.ua

MERCOR FIRE PROTECTION SYSTEMS S.C. S.R.L. Romania www.mercor.ro

- Orum Centura Chitila:
- Mogosoaia, no 3, floor 4
- 💿 Oras Chitila, Ilfov RO-077045
- +40 371 324 182
- +40 372 877 070
- 🖂 romania@mercor.com.pl

MERCOR TECRESA Spain

Parque Tecnológico Legatec. www.mercortecresa.com

- O/ Margarita Salas nº 6
- 28919 Leganés (Madrid)
- +34 91 428 22 60
- +34 91 428 22 62
- 🖂 info@mercortecresa.com

MERCOR SLOVAKIA S.R.O. Slovakia

www.mercor-slovakia.sk

- Galvaniho 7/D
- 821 04 Bratislava
- S +421 2 2062 0040
- S +421 2 2062 0049
- 🖂 mercor@mercor-slovakia.sk



European Union European Regional Development Fund



MERCOR CZECH REPUBLIC S.R.O.

Czech Republic

Eetní 1122/1

www.mercor-czech.cz

9 721 00 Ostrava-Svinov

⊠ mercor@mercor-czech.cz

MERCOR - DUNAMENTI

Nemeskéri Kiss Miklós utca 39

🖂 godcenter@dunamenti.hu

www.mercor-uk.co.uk

📎 +44 (0) 0161 3598309

🖂 enquiries@mercor-fp.co.uk

MERCOR FIRE PROTECTION UK LTD

Unit P(10), Heywood Distribution Park,

Pilsworth Road, Heywood, OL10 2TT

TŰZVÉDELEM ZRT.

www.dunamenti.hu

S +36 30 919-0542

Hungary

2131 Göd

England

& +420 597 317 665

The product was developed within the framework of an innovative project entitled: "Comprehensive solutions in the scope of passive fire protection of buildings including the development of display line" subsidized with European funds.



Read more about our mcr THERM SYSTEMS for staircases

www.mercor.com.pl/en



CONTINUOUS ROOFLIGHT WITH SMOKE VENTS

> SMOKE AND VENTILATION VENTS

> > LOUVERED VENTS



SMOKE CURTAINS



SMOKE EXHAUST WINDOWS




ROOF HATCHES



FIXED SKYLIGHTS



CONTROL SYSTEMS



STAIRCASE SMOKE EXHAUST SYSTEMS

