


SMOKE CONTROL DAMPER

> mcr FID B	> mcr DOR	mcr WIP PROV/ mcr WIP PROV/V-M	> mcr WIP LD	> mcr WIP LDX
				
Smoke exhaust + Comfort ventilation EN 12101-8 / EN 1366-10 / EN-13501-4 001-05-CPR-2021	Smoke exhaust EN 12101-8 / EN 1366-10 / EN-13501-4 002-05-CPR-2022	Smoke exhaust + Comfort ventilation EN 12101-8 / EN 1366-10 / EN-13501-4 01-06-CPR-2024	Smoke exhaust + Comfort ventilation EN 12101-8 / EN 1366-10 / EN-13501-4 001-05-CPR-2022	Smoke exhaust + Comfort ventilation EN 12101-8 / EN 1366-10 / EN-13501-4 001-11-CPR-2025
Rectangular single - blade	Rectangular door	Rectangular multi - blade	Rectangular multi - blade	Rectangular multi - blade
200x200 ÷ 1200x800 [mm]	480x380 ÷ 1330x1330 [mm]	110x270 ÷ 1200x2300 [mm]	300x600 ÷ 1100x2300 [mm]	300x600 ÷ 1100x2300 [mm]
Bi-directional actuator type BE, BEE, BEN (24V or 230V)	Mechanism spring loaded with fuse trigger	Bi-directional actuator type BE, BEE, BEN (24V or 230V)	Bi-directional actuator type BE, BEE, BEN (24V or 230V)	Bi-directional actuator type BE, BEN (24V or 230V)
C	C	C	C	C
min. 2	min. 2	min. 2	min. 2	min. 2
X	X	X	X	X
Fireproof boards + galvanised steel	Fireproof boards + galvanised steel	Fireproof boards + galvanised steel, coating ZN optional: stainless steel or 1.4404 acid proof steel	Galvanized steel housing selected stainless steel components	Galvanized steel housing selected stainless steel components

E120(v _{ed} h _{ed} i↔o)S1500 C ₁₀₀₀₀ MAmulti (in the distance)	E180(v _{ed} i↔o)S1500 C ₃₀₀ AAmulti (in the distance)	E120 (v _{ed} i↔o)S1000 C ₁₀₀₀₀ AAmulti*	E120 (v _{ev} i↔o)S1000 C ₁₀₀₀₀ AAmulti	E120 (v _{ev} i↔o)S1500 C ₁₀₀₀₀ AAmulti E120 (v _{ev} i↔o)S500 C ₁₀₀₀₀ AAmulti
-	-	-	125 mm	125 mm
E120(v _{ed} h _{ed} i↔o)S1500 C ₁₀₀₀₀ MAmulti (in the distance)	E180(v _{ed} i↔o)S1500 C ₃₀₀ AAmulti (in the distance)	E120 (v _{ed} i↔o)S1000 C ₁₀₀₀₀ AAmulti	E120 (v _{ev} i↔o)S1000 C ₁₀₀₀₀ AAmulti	E120 (v _{ev} i↔o)S1500 C ₁₀₀₀₀ AAmulti E120 (v _{ev} i↔o)S500 C ₁₀₀₀₀ AAmulti
-	-	-	125 mm	125 mm
E120(v _{ed} h _{ed} i↔o)S1500 C ₁₀₀₀₀ MAmulti (in the distance)	X	X	X	X
-	X	X	X	X
✓	X	✓	X	X
X	damper next to damper, damper over damper	damper next to damper, damper over damper	X	X
✓	X	X	X	X
✓	-	✓	X	X
vertical and horizontal position: E120(v _{ed} h _{ed} i↔o)S1500 C ₁₀₀₀₀ MAmulti	vertical position: E180(v _{ed} i↔o)S 1500 C ₃₀₀ AAmulti	E120 (v _{ed} i↔o)S1000 C ₁₀₀₀₀ AAmulti	X	X
vertical and horizontal position: E120(v _{ed} h _{ed} i↔o)S1500 C ₁₀₀₀₀ MAmulti	vertical position: E180(v _{ed} i↔o)S 1500 C ₃₀₀ AAmulti	E120 (v _{ed} i↔o)S1000 C ₁₀₀₀₀ AAmulti	X	X
-	-	-	200 mm (acc. to norm)	200 mm (acc. to norm)
N/A	N/A	N/A	N/A	N/A
-	-	-	75 mm	75 mm
10 000	300	10 000	10 000	10 000
✓	✓	✓	✓	✓



> Gdansk
 Grzegorza z Sanoka 2
 80-408 Gdansk, Poland
 (+48) 58 341 42 45
 hw.export@mercor.com.pl



PRODUCT BROCHURE FIRE AND SMOKE CONTROL DAMPERS

www.mercor.com.pl/en

f
www.facebook.com/mercorlv

in
www.linkedin.com/company/mercorlv

yt
www.youtube.com/@mercorlv

FIRE DAMPERS

SMOKE CONTROL DAMPER

Damper type	> mcr FID PRO	> mcr FID S/S p/O	> mcr FID S/S c/P	> mcr FID S/S p/P	> mcr FID 240L	> mcr WIP/S	> mcr WIP PRO/S	> mcr FID WING	> mcr ZIPP	> mcr WIP/T	> mcr WIP PRO/T	> mcr WIP PRO/V mcr WIP PRO/V-M	> mcr FID S/V p/P mcr FID S/V-M p/P
Properties													
Type of installation / application	Comfort ventilation	Comfort ventilation	Comfort ventilation	Comfort ventilation	Comfort ventilation	Comfort ventilation	Comfort ventilation	Comfort ventilation	Comfort ventilation	Transfer damper	Transfer damper	Smoke exhaust + Comfort ventilation	Smoke exhaust + Comfort ventilation
CE Standards / fire resistance / fire classification	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 15650 / EN 1366-2 / EN 13501-3	EN 12101-8 / EN 1366-10 / EN-13501-4	EN 12101-8 / EN 1366-10 / EN-13501-4
Declaration of performance	003-05-CPR-2015	004-05-CPR-2015	006-05-CPR-2015	004-05-CPR-2015	001-05-CPR-2025	001-05-CPR-2015	009-05-CPR-2016	002-05-CPR-2021	002-05-CPR-2015	001-05-CPR-2015	009-05-CPR-2016	010-05-CPR-2016	001-05-CPR-2018
Damper type	Low resistance rectangular single - blade	Circular single - blade	Low resistance rectangular single - blade	Rectangular single - blade	Rectangular single - blade	Rectangular multi - blade	Rectangular multi - blade	Butterfly damper	Round valve	Rectangular multi - blade	Rectangular multi - blade	Rectangular multi - blade	Rectangular single - blade
Dimensions	D100 + D315 [mm]	D125 + D630 [mm]	for v_e i h_e : 100x100 + 800x400 [mm] for v_e : 100x100 + 1000x800 [mm]	200x200 + 1500x1200 [mm] 200x200 + 1200x1500 [mm] maximum damper's cross-section: 1,8 m ²	200x200 + 1050x1000 [mm]	120x160 + 1000x1000 [mm] (Except dampers whose height ends in a dimension between 36 and 54, e.g. 136-154, 236-254...)	for v_e : 110x270 + 900x1250 [mm] for h_e : 110x270 + 1000x1000 [mm]	D100, D125, D160, D200 [mm]	D100, D125, D160, D200 [mm]	120x160 + 1000x1000 [mm] (Except dampers whose height ends in a dimension between 36 and 54, e.g. 136-154, 236-254...)	110x270 + 900x1250 [mm]	horizontal axis of rotation (v_{ev} and v_{edw}): 110x263 + 900x1250 [mm] vertical axis of rotation (v_{ev}): 110x263 + 1250x1250 [mm] horizontal axis of rotation (v_{ev} , h_{ed}): 110x263 + 1250x1250 [mm]	200x200 + 1500x1000 [mm] 200x200 + 1000x1500 [mm] maximum damper's cross-section: $\leq 1,5m^2$
Trigger and control mechanism	Actuator with thermal trigger (72°C or 95°C) type BFL, BFN, BF, MLF (24V - 230V) Mechanism spring loaded with fuse trigger (74°C or 95°C) RST option -electromagnetic trigger	Actuator with thermal trigger (72°C or 95°C) type BFL, BFN, BF (24V - 230V) Mechanism spring loaded with fuse trigger (74°C or 95°C) RST option -electromagnetic trigger	Actuator with thermal trigger (72°C or 95°C) type BFL, BFN, BF, MLF (24V - 230V) Mechanism spring loaded with fuse trigger (74°C or 95°C) RST option -electromagnetic trigger	Actuator with thermal trigger (72°C or 95°C) type BFL, BFN, BF (24V - 230V) Mechanism spring loaded with fuse trigger (74°C or 95°C) RST option -electromagnetic trigger	Actuator with thermal trigger (72°C or 95°C) type BFL, BFN, BF (24V - 230V)	Actuator with thermal trigger (72°C or 95°C) type BFL, BFN, BF (24V - 230V)	Actuator with thermal trigger (72°C or 95°C) type BFL, BFN, BF (24V - 230V) Mechanism KW1/S RST option -electromagnetic trigger	Mechanism spring loaded with fuse trigger	Mechanism spring loaded with fuse trigger (74°C or 95°C) RST option -electromagnetic trigger	Actuator with thermal trigger (72°C or 95°C) type BFL, BFN, BF (24V - 230V) Mechanism KW1/S RST option -electromagnetic trigger	Actuator with thermal trigger (72°C or 95°C) type BFL, BFN, BF (24V - 230V) Mechanism KW1/S RST option -electromagnetic trigger	Bi-directional actuator type BE, BEE, BEN (24V or 230V)	Bi-directional actuator type BE, BEE, BEN (24V or 230V)
Casing tightness class [A/B/C] acc. to PN-EN 1751	C	C	C	C	C	C	C	-	-	C	C	C	C
Damper blade tightness in closed position [1/2/3/4] acc. to PN-EN 1751	min. 2	min. 2	min. 2	min. 2	min. 2	min. 2	min. 2	min. 2	min. 2	min. 2	min. 2	min. 2	min. 2
ATEX execution	✓	✓	✓	✓	✓	✓	✓	X	✓	✓	✓	X	X
Casing material	Galvanised steel coatin. Optional: stainless steel, acid-proof steel	Galvanised steel coatin. Optional: stainless steel, acid-proof steel	Galvanised steel coatin. Optional: stainless steel, acid-proof steel	Galvanised steel coatin. Optional: stainless steel, acid-proof steel	Galvanised steel coatin. Optional: stainless steel, acid-proof steel	Galvanised steel coatin. Optional: stainless steel, acid-proof steel	Galvanised steel coatin. Optional: stainless steel, acid-proof steel	Fireproof boards + galvanised steel, coating ZN optional: stainless steel or 1.4404 acid proof steel	Painted steel	Painted steel	Galvanised steel coatin. Optional: stainless steel, acid-proof steel	Galvanised steel coatin. Optional: stainless steel, acid-proof steel	Fireproof boards + galvanised steel, coating ZN optional: stainless steel or 1.4404 acid proof steel

Installation														
Rigid walls/shafts	Classification	E120 (v_e i ↔ o) S	E1240 (v_e i ↔ o) S	E160 (v_e i ↔ o) S E120 (v_e i ↔ o) S	E120 (v_e i ↔ o) S	E1120 (v_e i ↔ o) S E120 (v_e i ↔ o) S	E120 (v_e o → i) S E120 (v_e i ↔ o) S E180 (v_e o → i) S	E120 (v_e i ↔ o) S E120 (v_e i ↔ o) S	E1180 (v_e i ↔ o) S	E120 (v_{edw} i ↔ o) S1000 C ₁₀₀₀₀ AA multi E120 (v_{edw} i ↔ o) S1000 C ₁₀₀₀₀ AA multi	E120 (v_{edw} i ↔ o) S1500 C ₁₀₀₀₀ AA multi E120 (v_{edw} i ↔ o) S1000 C ₁₀₀₀₀ AA multi			
	Min. partition thickness	120 mm/125 mm	110 mm	120 mm/125 mm	110 mm	150 mm	120 mm	120 mm	100 mm 100 mm	110 mm	120 mm	120 mm	125 mm	120 mm
Light-weight walls/shafts	Classification	E120 (v_e i ↔ o) S	X	X	E120 (v_e i ↔ o) S	E120 (v_e i ↔ o) S E160 (v_e i ↔ o) S	E120 (v_e o → i) S E120 (v_e i ↔ o) S E180 (v_e o → i) S	X	E1180 (v_e i ↔ o) S	E120 (v_{edw} i ↔ o) S1000 C ₁₀₀₀₀ AA multi E120 (v_{edw} i ↔ o) S1000 C ₁₀₀₀₀ AA multi	E120 (v_{edw} i ↔ o) S1500 C ₁₀₀₀₀ AA multi			
	Min. partition thickness	125 mm	125 mm	125 mm	125 mm	X	X	125 mm	100 mm 100 mm	125 mm	X	125 mm	125 mm	125 mm
Ceillings	Classification	E120 (h_e i ↔ o) S	X	X	E190 (h_e i ↔ o) S E120 (h_e i ↔ o) S	E120 (h_e i ↔ o) S E160 (h_e i ↔ o) S	E120 (h_e o → i) S E120 (h_e i ↔ o) S	X	X	E120 (h_{ed} i ↔ o) S1000 C ₁₀₀₀₀ AA multi	E120 (h_{ed} i ↔ o) S1000 C ₁₀₀₀₀ AA multi			
	Min. partition thickness	150 mm	150 mm	150 mm	150 mm	X	X	150 mm	150 mm 100 mm	150 mm	X	X	-	-
Installation outside the vertical building partition		✓	X	X	✓	X	X	X	X	X	X	X	✓	✓
Battery assembly/Modules		-	-	X	Series assembly	X	X	X	-	-	X	X	Max. 4 dampers with dimensions: with horizontal axis of rotation: 110x270 to 1060x1025 [mm] or with vertical axis of rotation 270x110 to 960x1125 [mm]	20m ² : with vertical axis of rotation, mechanism at the top or/and at the bottom of the battery - for the partition by min. thickness 120 mm
Vertical axis of rotation		✓	✓	✓	✓	X	X	X	✓	✓	✓	✓	✓	✓
Dry assembly with mineral wool		✓	X	✓	X	X	X	X	✓	X	X	X	X	X
Multi - zone		-	-	-	-	-	-	-	-	-	-	-	E120 (v_{ed} h_{ed} i ↔ o) S1000 C ₁₀₀₀₀ AA multi	E120 (v_{ed} h_{ed} i ↔ o) S1000 C ₁₀₀₀₀ AA multi
Single - zone		-	-	-	-	-	-	-	-	-	-	-	E120 (v_{ed} h_{ed} i ↔ o) S1000 C ₁₀₀₀₀ AA multi	E120 (v_{ed} h_{ed} i ↔ o) S1000 C ₁₀₀₀₀ AA multi
Minimum distance damper / wall		60 mm/10 mm	200 mm (acc. to norm)	30 mm	60 mm (PP)	200 mm (acc. to norm)	200 (acc. to norm)	200 (acc. to norm)	50 mm	200 mm (acc. to norm)	200 mm (acc. to norm)	200 mm (acc. to norm)	200 mm (acc. to norm) not applicable to batteries and v_{ed} featu	200 mm (acc. to norm) not applicable to batteries and v_{ed} featu
Minimum distance damper / partition		75 mm/10 mm	75 mm (acc. to norm)	75 mm (acc. to norm)	75 mm (acc. to norm)	75 mm (acc. to norm)	75 mm (acc. to norm)	75 mm (acc. to norm)	75 mm (acc. to norm)	75 mm (not applicable to v_{ed} feature)	75 mm (not applicable to v_{ed} feature)			
Minimum distance damper / ceiling		75 mm/10 mm	75 mm	20 mm	75 mm	75 mm	75 mm	75 mm	75 mm	75 mm	75 mm	75 mm	-	75 mm
Operating life cycles		10 000	50	10 000	10 000	10 000	10 000	10 000	50	50	10 000	10 000	10 000	10 000
Certified installation with a masking grille		-	-	-	-	-	-	-	- / Anemostat	✓	✓	✓	✓	✓