



smoke exhaust vents,
skylights,
roof access hatches

mcr
PROLIGHT

We provide safety

NATURAL SMOKE EXHAUST SYSTEM



The fire causes the release of large amounts of smoke and hot gases in the building that can be dangerous for people inside. The priority in such a case is to evacuate people as soon as possible to reduce losses of properties. In order to achieve this, it is important to remove smoke from evacuation routes and to lower the smoke temperature, which also mitigates the risk of the building structure damage.

In order to achieve the above goals, natural smoke exhaust systems are designed with their basic elements,

which include **mcr PROLIGHT** smoke exhaust ventilators and control devices.

Mercor Light&Vent sp. z o.o. offers comprehensive solutions within the area of fire safety for various types of premises, starting from large format halls to staircase smoke exhaust systems.

In order to meet the various requirements of our customers, we have elaborated a whole range of smoke exhaust vents that additionally may have the function of ventilation, spot skylights or regular roof access hatches.



Mercor Light&Vent's mission is to deliver safety to building users by providing them with comprehensive fire protection. For over 35 years, we have been offering our business partners, at every stage of the investment process, products and services they can always trust. As a leader of modern technologies in the fire protection industry, we introduce new solutions that are ahead of the norm, and are additionally characterized by high quality and aesthetic workmanship.

smoke exhaust vents,
skylights,
roof access hatches

**mcr
PROLIGHT**

TYPES OF mcr PROLIGHT SMOKE EXHAUST VENTS


SINGLE LEAF VENTS



mcr PROLIGHT - C
with straight base (square)




mcr PROLIGHT - E
with straight base (rectangular)




mcr PROLIGHT - NG-A
with skew base

DOUBLE LEAF VENTS



mcr PROLIGHT - DVP
with straight base



mcr PROLIGHT - DVPS
with skew base



ADVANTAGES OF mcr PROLIGHT SMOKE EXHAUST VENTS

FUNCTION

Spot smoke vent may provide several functions at the same time, e.g.: smoke and heat exhaust, daily ventilation, supply of daylight and roof access.



CERTIFICATES

Product classification according to EN 12101-2, marked CE.



A WIDE RANGE OF DIMENSIONS

The ability to produce a product „made to measure“ according to customer requirements.



mcr PROLIGHT smoke vents obtained environmental declaration showing environmental impact of the product – from sources extraction to transport.



DESIGN

The availability of various types of spot vents with different shapes as well as equipment elements.



CHOICE OF ACTIVE SURFACE

Adjusting active area of the smoke vent by optional fitting elements that enhance its parameters (wind deflectors, inlet deflectors).



OPERATIONAL RELIABILITY

Excellent technical parameters of smoke exhaust vents ensure their operational reliability.



NON-STANDARD SOLUTIONS

The preparation of non-standard variants of vents according to an architect's vision is also possible on request.





mcr PROLIGHT SMOKE EXHAUST VENTS – C/E TYPE

Single leaf vents with straight base

AERODYNAMICAL ACTIVE AREA

With the application of optional elements increasing the active smoke exhaust surface (wind and inlet deflectors), it is possible to reach the max. value of **3.24 m² (type C)** or **4.05 m² (type E)**.



LEAF FILLING

Leaf filling that affects heat transfer coefficient U:

- multi-chamber polycarbonate panel —
- acrylic dome —
- solid polycarbonate dome —
- sandwich panel ALU —
- single and multi-layer filling —



DIMENSIONS

- Size range for C type vents (square)
100 x 100 cm ÷ 200 x 200 cm
- Size range for E type vents (rectangular)
100 x 50 cm ÷ 200 x 250 cm



CONSTRUCTION OPTIONS

A whole range of smoke exhaust vents types and a wide portfolio of optional elements can be applied in order to implement the most demanding customer requests.



CONTROL

Controls can be selected according to project requirements:

- **smoke exhaust:** pneumatic, electric (24 V- or 48 V-*)
- **ventilation:** electric (24 V-/48 V-*/230 V~)

(*) for Actulux controls

Also available as smoke vents with daily ventilation and as only ventilation vents, skylights or roof access hatches.





mcr PROLIGHT SMOKE EXHAUST VENTS – NG-A TYPE

Single leaf vents with skew base

AERODYNAMICAL ACTIVE AREA

Max. active surface that can be reached is **4.53 m²**.



LEAF FILLING

Leaf filling that affects heat transfer coefficient U:


- multi-chamber polycarbonate panel —
- acrylic dome —
- solid polycarbonate dome —
- sandwich panel ALU —
- single and multi-layer filling —



DIMENSIONS

Size range for vents:

100 x 100 cm ÷ 210 x 210/200 x 300 cm



CONSTRUCTION OPTIONS

The possibility of various execution variants of vents in line with the philosophy of products „tailored to the needs“ of the customer.



CONTROL

Controls can be selected according to project requirements:

- **smoke exhaust:** pneumatic, electric (24 V- or 48 V-*)
- **ventilation:** electric (24 V-/48 V-*/230 V~)

(*) for Actulux controls

Also available as smoke vents with daily ventilation and as only ventilation vents, skylights or roof access hatches.





mcr PROLIGHT SMOKE EXHAUST VENTS – DVP/DVPS TYPE

Double leaf vents with straight and skew base

AERODYNAMICAL ACTIVE AREA

DVP type smoke vents can reach the max. aerodynamical active area of **6.66 m²** with the application of elements increasing the active area (such as wind and inlet deflectors). And for DVPS type vents, the maximum value of the active smoke removal area is **6.39 m²** (without additional elements).

LEAF FILLING

Leaf filling that affects the heat transfer coefficient U:


- multi-chamber polycarbonate panel —
- sandwich panel ALU —
- single and multi-layer filling —



DIMENSIONS

Size range for vents:

120 x 250 cm ÷ 300 x 300 cm



CONSTRUCTION OPTIONS


A range of options is available for the execution of smoke exhaust vents as well as additional elements to tailor the offer to the customer's requirements.



CONTROL

- smoke exhaust: pneumatic, electric (24 V-)
- ventilation: electric (230 V~)

Also available as smoke exhaust ventilation or daily ventilation vents.






mcr PROLIGHT SKYLIGHTS

Skylights – fixed and with ventilation function with straight /skew /overlay base



DIMENSIONS

- (square C type)
80 x 80 cm ÷ 200 x 200 cm
- (rectangular E type)
80 x 90 cm ÷ 195 x 300 cm
- (skew base NG-A type)
80 x 80 cm ÷ 200 x 300 cm



BASE


- height: 16–75 cm
- material: steel, aluminium
- thermal insulation with mineral wool or PIR panel
- possible to apply on existing plinth



LEAF FILLING

- multi-chamber polycarbonate
- domes: acrylic or solid polycarbonate
- multivariable single and multi-layer filling

CONTROL ventilation: electric (230 V~)



mcr PROLIGHT HATCHES

Roof access hatches with straight /skew base



DIMENSIONS

- (square C type)
80 x 80 cm ÷ 140 x 140 cm
- (rectangular E type)
80 x 90 cm ÷ 140 x 150 cm
- (skew base NG-A type)
90 x 90 cm ÷ 150 x 150 cm



BASE

- height: 25–75 cm
- material: steel, aluminium
- thermal insulation with mineral wool or PIR panel
- possible to apply on existing plinth



LEAF FILLING

- multi-chamber polycarbonate
- domes: acrylic or solid polycarbonate
- multivariable single and multi-layer filling



Mercor Light&Vent sp. z o.o.
ul. Grzegorza z Sanoka 2
80-408 Gdańsk, Poland
tel. +48 58 341 42 45
export@mercors.com.pl

MERCOR UKRAINE SP. Z O.O.
Ukraine

www.mercor.com.ua

📍 9B Yaroslava Mudrogo str.

📍 79016 Ukraine, Lviv

☎ +380 322420346

✉ info@mercors.com.ua

MERCOR FIRE PROTECTION
SYSTEMS S.C. S.R.L.

Romania

www.mercor.ro

📍 Drum Centura Chitila:

📍 Mogosoaia, no 3, floor 4

📍 Oras Chitila, Ilfov RO-077045

☎ +40 371 324 182

☎ +40 372 877 070

✉ romania@mercors.com.pl

MERCOR TECRESA
PROTECCIÓN PASIVA, S.L.

Spain

mercortlv.es

📍 Parque Tecnológico Legatec.

📍 C/ Margarita Salas nº 6

📍 28919 Leganés (Madrid)

☎ +34 911 169 616

✉ info@mercortlv.com

MERCOR SLOVAKIA S.R.O.
Slovakia

www.mercor-slovakia.sk

📍 Galvaniho 7/D

📍 821 04 Bratislava

☎ +421 2 2062 0040

☎ +421 2 2062 0049

✉ mercor@mercorslovakia.sk

MERCOR CZECH REPUBLIC S.R.O.
Czech Republic

www.mercor-czech.cz

📍 Letní 1122/1

📍 721 00 Ostrava-Svinov

☎ +420 597 317 665

✉ mercor@mercors-czech.cz

MERCOR HUNGARY KFT.
Hungary

mercors.hu

📍 Teréz körút 55-57. Building A, 2nd floor

📍 1062 Budapest

✉ info@mercors.hu

MERCOR FIRE PROTECTION UK LTD
England

mercors-uk.co.uk

📍 Unit P(10), Heywood Distribution Park,

📍 Pilsworth Road, Heywood, OL10 2TT

☎ +44 (0) 0161 3598309

✉ enquiries@mercors-fp.co.uk

CONTINUOUS
ROOFLIGHT WITH
SMOKE VENTS



SMOKE AND
VENTILATION
VENTS



LOUVERED
VENTS



SMOKE
CURTAINS



SMOKE
EXHAUST
WINDOWS




ROOF
HATCHES



FIXED
SKYLIGHTS



CONTROL
SYSTEMS



STAIRCASE SMOKE
EXHAUST SYSTEMS



European
Funds
Smart Growth

European Union
European Regional
Development Fund



The product was developed within the framework of an innovative project entitled:
***"Comprehensive solutions in the scope of passive fire protection
of buildings including the development of display line"***
subsidized with European funds.



Read more about
our product in the
mcr PROLIGHT series

www.mercors.com.pl/en

