



roof and façade
mounted
louvered vents

mcr LAM



We provide safety

NATURAL SMOKE EXHAUST SYSTEM

The **mcr LAM roof-mounted and façade-mounted** louvered vents are intended for the removal of smoke and toxic fire gases as well as for comfort ventilation.

These devices, together with the **mcr PROLIGHT** wing smoke vents and the **mcr PROSMOKE** smoke curtains, make up the basic assortment enabling the construction of a complete natural smoke exhaust system.

They can be used: in warehouses, industrial or sports halls and in commercial facilities, especially in passages and atriums, as well as in high-rise buildings. They have been designed in such a way that the method of water drainage from their surface guarantees

high tightness parameters, regardless of the location in which the device will be installed (from installation in flat roofs, through roofs with any slope).

They can be successfully used for natural comfort ventilation in strong winds, which is particularly important in high-rise buildings. The use of smoke louvered vents can also be an excellent solution in the case of roofs with many elements protruding above the slope, which often prevents the full opening of the vent's leaves.

The **mcr LAM** series products are approved for use in all European Union countries on the basis of a certificate of compliance with the European Standard **PN-EN-12101-2**.



Mercor Group's mission is to deliver safety to building users by providing them with comprehensive fire protection. For over 35 years, we have been offering our business partners, at every stage of the investment process, products and services they can always trust. As a leader of modern technologies in the fire protection industry, we introduce new solutions that are ahead of the norm, and are additionally characterized by high quality and aesthetic workmanship.

roof and façade
mounted
louvered vents

mcr LAM

CONSTRUCTION

The **bases** of the louvered vents are made of galvanized steel plate with a thickness of 1.25 mm to 2 mm and can be insulated from the outside. Up to a height of 20 cm, the base of the louvered vents is one-piece and the maximum thickness of its insulation is 20 mm. Above 20 cm, two-piece bases are available. The upper element then has a height of 15 cm (insulation max. 20 mm), while the lower element is a supplement to the total height of the base (insulation up to 100 mm). The lower part of the base can be additionally equipped with: a set of flashings for profiled sheets, a burglary grid or safety net.

- | | |
|---|---|
| 1 | blades |
| 2 | blade drive
(electric or pneumatic actuator) |
| 3 | wind deflector |
| 4 | single-piece base |
| 5 | two-piece base |

The **blades** are made of aluminum profiles with a multi-chamber polycarbonate (standard: clear or opal). Opaque filling with aluminum sheet is also available. The blades are connected in such a way that they rotate 90 degrees at the same time. The tightness of the vent is ensured by the special construction of the blades and the base and the EPDM gasket placed between them. **mcr LAM** smoke vents variant is equipped with a set of wind deflectors increasing its active surface.

CONSTRUCTION OF THE LOUVERED SMOKE EXHAUST VENT mcr LAM




Fig. 1 Louvered vent with one-piece base




Fig. 2 Louvered vent with two-piece base




Photo. I-II Vent blades made of aluminum profiles filled with polycarbonate

EXECUTION OPTIONS

- » painting the base
- » painting metal elements of the blades
- » painting the deflectors and rain shield
- » anti-burglar grind and safety net
- » aluminum support of the base enabling installation on a profiled sheet roof
- » limit switch or opening and/or closing signalling

- » possibility of mounting on roofs with any slope and in façades
- » resistance of the vents in the open position to wind action
- » low consumption of electricity or compressed CO₂ gas by the controls
- » easy to place on the roof – the blades of the louvered vents do not extend beyond the geometric dimension of the device (especially important in tall buildings or those where there is a problem with finding free space on the roof)



Zdjęcie. III-IV Façade mounted mcr LAM vents equipped in rain shields

CLASSIFICATION

SL250 ÷ 1300 for electric actuators

SL 550 ÷ 2000 for pneumatic actuators

WL1500 for all types of louvered vents

B300 resistance of vents to high temperature of 300°C

F fire reaction class for other elements

T(-25) resistance of vents to low temperature of -25°C

Re300 operational reliability during 300 cycles of opening and closing to smoke exhaust position (vent with E1 electric control and C1, C2, C3 pneumatic control)

The time of opening the louvered vents to the operating position does not exceed 60 s.



„MERCOR” S. A.
ul. Grzegorza z Sanoka 2
80-408 Gdańsk, Poland
tel. + 48 58 341 42 45
export@mercors.com.pl

MERCOR UKRAINE SP. Z O.O.
Ukraine

www.mercor.com.ua

📍 Scheptyckich 26

📍 79-016 Lviv

☎ +380 32 240 34 47

☎ +380 32 240 34 07

✉ info@mercors.com.ua

MERCOR FIRE PROTECTION
SYSTEMS S.C. S.R.L.

Romania

www.mercor.ro

📍 Drum Centura Chitila

📍 Mogosoia, no 3, floor 4

📍 Oras Chitila, Ilfov RO-077045

☎ +40 371 324 182

☎ +40 372 877 070

✉ romania@mercors.com.pl

MERCOR TECRESA

Spain

Parque Tecnológico Legatec.

www.mercortecresa.com

📍 C/ Margarita Salas nº 6

📍 28919 Leganés (Madrid)

☎ +34 91 428 22 60

☎ +34 91 428 22 62

✉ info@mercortecresa.com

MERCOR SLOVAKIA S.R.O.

Slovakia

www.mercor-slovakia.sk

📍 Galvaniho 7/D

📍 821 04 Bratislava

☎ +421 2 2062 0040

☎ +421 2 2062 0049

✉ mercor@mercorslovakia.sk

MERCOR CZECH REPUBLIC S.R.O.

Czech Republic

www.mercor-czech.cz

📍 Letní 1122/1

📍 721 00 Ostrava-Svinov

☎ +420 597 317 665

✉ mercor@mercors-czech.cz

MERCOR - DUNAMENTI
TŰZVÉDELEM ZRT.

Hungary

www.dunamenti.hu

📍 Nemeskéri Kiss Miklós utca 39

📍 2131 Cöd

☎ +36 30 919-0542

✉ godcenter@dunamenti.hu

MERCOR FIRE PROTECTION UK LTD

England

www.mercor-uk.co.uk

📍 Unit P(10), Heywood Distribution Park,

📍 Pilsworth Road, Heywood, OL10 2TT

☎ +44 (0) 0161 3598309

✉ enquiries@mercors-fp.co.uk

CONTINUOUS
ROOFLIGHT WITH
SMOKE VENTS



SMOKE AND
VENTILATION
VENTS



LOUVERED
VENTS



SMOKE
CURTAINS



SMOKE
EXHAUST
WINDOWS




ROOF
HATCHES



FIXED
SKYLIGHTS



CONTROL
SYSTEMS



STAIRCASE SMOKE
EXHAUST SYSTEMS



European
Funds
Smart Growth


European Union
European Regional
Development Fund



The product was developed within the framework of an innovative project entitled:

***“Comprehensive solutions in the scope of passive fire protection
of buildings including the development of display line”***

subsidized with European funds.



Read more
about our louvered
smoke exhaust
vents mcr LAM

www.mercor.com.pl/en

